

## JULIET apron (without sleeves) (PPE - category I)



### FIELD OF APPLICATION

JULIET apron resists to standard cleaning products. It is valued for its flexibility, its lightness and excellent tear resistance.

**MATERIAL:** polyurethane on polyamide support

### FEATURES

- **Colour:** white, blue and green
- **Thickness:** 400 µm (± 10%)
- **Weight:** 170 g/m<sup>2</sup> (± 10%)
- Standard **dimensions** (width x height in cm): 90 x 115

Aprons with stainless steel brass rings and eyelets

Food safe polypropylene adjustment loop

Detectable plastic hook and polyester braided elastic



Blanc  
White

Rouge  
Red

Jaune  
Yellow

Bleu  
Blue

Vert  
Green

### NORMS & REGULATIONS

- Base material in accordance with **EC N° 1935/2004 Regulation**, articles 3 and 4 on materials and articles intended to come into contact with food.
- Base material in accordance with **UE N°10/2011 Regulation** on rubber materials and articles intended to come into contact with food. This PPE may be put in fortuitous contact with all types of food.
- Apron in accordance with **Article 33 of the REACH Regulation N°1907/2006** and its amendments on products containing SVHC.



### CLEANING CONDITIONS

**Cleaning:** wash and brush the apron in hot soapy water (40°C) or in a mixture of water and a gentle detergent.

**Rinsing:** with water. Do not use toxic products to clean or rinse the apron. **Storage:** After cleaning, store in a dark, dry, well-ventilated place. The apron must be replaced when it shows signs of wear and tear.

**With a proper use and a good maintenance, your apron lasts longer!**

N° intrastat : 39262000

## JULIET apron (without sleeves) (PPE - category I)



- This apron complies with the regulation (UE) **PPE 2016/425** and the standard **NF EN ISO 13688** (2013).
- Claimed mechanical properties: abrasion, tear, tensile and puncture resistance.

### PERFORMANCE LEVELS

Type of test	Standard	Performance
Abrasion resistance	EN 12947-2	>100 000 frictions
Trapezoidal tear resistance	EN ISO 9073-4	>40 N
Tensile resistance	EN ISO 13934-1	>140 N
Puncture resistance	EN 863	>20 N

N° intrastat : 62102000

*Bien plus que la sécurité*  
More than just safety