

**TPLUS TUNIC WITH SPLIT LEG & with sleeves** (PPE - category III)



**FIELD OF APPLICATION**


The TPLUS tunic is made with 100% food contact approved stainless steel. It is used by butchers in meat industries, Horeca, supermarkets and many other fields such as textile industry... It ensures cut-protection against any risks with hand knives, hand cutting tools or stabbing.

**MATERIAL:** Stainless steel chainmail. Food contact

**FEATURES**


**Bust:**

- Wire diameter: 0,5 mm
- Internal diameter of the rings: 3 mm
- External diameter of the rings: 4 mm



**Sleeve(s):** EN ISO 13998 (2003) performance level 1

- Wire diameter: 0,4 mm
- Internal diameter of the rings: 3,2 mm
- External diameter of the rings: 4 mm



Ultralight sleeves

Self-closing wrist closure system with stainless steel spring.

Straps attached to the tunic with stainless steel plates.

Adjustable waist belt and back strap 100 % polyurethane (food contact according to EU regulation 10/2011) and polyacetal buckles.

You can add an hygienic cover or a press-studs apron for maximum hygiene and ease of cleaning.

Blank stainless steel plate on the back (possibility of customized printing on demand).



**Ultralight sleeves for optimal comfort !**



**NORMS & REGULATIONS**

This tunic complies with the regulation (UE) EPI 2016/425 (2016).

**Bust:** EN ISO13998 (2003) performance level 2 (suitable for boning operations).

**Sleeves:** EN ISO13998 (2003) performance level 1.

**Notified body in charge of the certification:** N° 00556 Prüf und Zertifizierungsstelle Nahrungsmittel und Verpackung - Fachbereich Nahrungsmittel - Lortzingstrasse 2 - D - 55127 Mainz

**Notified body involved in manufacturing control:** N° 0333 AFNOR certification  
11 rue Francis De Pressensé - 93571 - La Plaine Saint-Denis



**CLEANING CONDITIONS**

**Cleaning / Disinfection:** PPE can be cleaned using a suitable washing gun, by soaking, by vigorous brushing or in a washing machine. In all cases, the water with added product must be at a maximum temperature of 63 ° C.

Warning : the technical sheet of the product used refers to a maximum water temperature, which may be lower.

Particular attention to dosage and temperature must be observed in the case of using alkaline chlorinated or acidic products.

Use only products authorized by the veterinary services. The use of chlorine in large doses and at high temperature is not recommended.

**Disinfection:** High temperature disinfection can be done with clean water of a minimum of 82 ° C up to a maximum temperature of 90 ° C, in a machine, by soaking or sprinkling.

**Drying and Storage:** Forced drying by hot or natural air ventilation but in a dry and ventilated place. Store in a cool, dry place.

N° intrastat : 73239390

*Bien plus que la sécurité*  
More than just safety



Adresse postale : CS 40055 - 49170 - SAINT-GEORGES-SUR-LOIRE - France - E-mail : manulatex@manulatex.fr - Internet : www.manulatex.fr  
Site de Champocé-sur-Loire : 1 Rue du Mille - 49123 CHAMPTOCÉ-SUR-LOIRE - France - Tel : +33 (0)2 41 39 90 30 -  
Site de St-Germain-des-Prés : Zone Artisanale La Potherie - 49170 ST-GERMAIN-DES-PRÉS - Tel : +33 (0)2 41 39 90 30  
SAS au capital de 125 000 € - R.C.S. Angers B 332 107 036 (85 B 112) - Siret 332 107 036 00029 - APE 3299Z - TVA FR 73 332 107 036 - EORI FR 332 107 036 00029

**TPLUS TUNIC WITH SPLIT LEG & with sleeves** (PPE - category III)



**SIZE AND REFERENCES**

Sleeves	Width x height (cm)	Reference	Weight (grams)	Operator's size (cm)	Waist / chest measurement (cm)
Manches 65 cm <i>Sleeves 65 cm</i>	50 x 100	<b>OXTU730.8S4.710DG5</b>	2580 g	148 - 190	80 - 110
	56 x 115	<b>OXTU730.8M7.710DG5</b>	3140 g	158 - 220	90 - 120
	56 x 125	<b>OXTU730.8M9.710DG5</b>	3260 g	165 - 220	
	64 x 125	<b>OXTU730.8L9.710DG5</b>	3500 g	165 - 220	100 - 140
Manches 75 cm <i>Sleeves 75 cm</i>	56 x 115	<b>OXTU730.8M7.710DG7</b>	3410 g	158 - 220	90 - 120
	64 x 125	<b>OXTU730.8L9.710DG7</b>	3790 g	165 - 220	100 - 140

N° intrastat : 73239390

*Bien plus que la sécurité*  
More than just safety



Adresse postale : CS 40055 - 49170 - SAINT-GEORGES-SUR-LOIRE - France - E-mail : manulutex@manulutex.fr - Internet : www.manulutex.fr  
 Site de Champtocé-sur-Loire : 1 Rue du Mille - 49123 CHAMPTOCÉ-SUR-LOIRE - France - Tel : +33 (0)2 41 39 90 30 -  
 Site de St-Germain-des-Prés : Zone Artisanale La Potherie - 49170 ST-GERMAIN-DES-PRÉS - Tel : +33 (0)2 41 39 90 30  
 SAS au capital de 125 000 € - R.C.S. Angers B 332 107 036 (85 B 112) - Siret 332 107 036 00029 - APE 3299Z - TVA FR 73 332 107 036 - EORI FR 332 107 036 00029