

TUNIC T+ without sleeves (PPE - category III)




FIELD OF APPLICATION

The TPLUS tunic is made with 100% food contact approved stainless steel. It is used by butchers in meat industries, Horeca, supermarkets and many other fields such as textile industry... It ensures cut-protection against any risks with hand knives, hand cutting tools or stabbing.

MATERIAL: Stainless steel chainmail. Food contact

FEATURES

- Wire diameter: 0,5 mm
- Internal diameter of the rings: 3 mm
- External diameter of the rings: 4 mm



Straps attached to the tunic with stainless steel plates
Adjustable waist belt and back strap 100 % polyurethane (food contact according to EU regulation 10/2011) and polyacetal buckles
Equipped with 2x3 press studs in order to adapt a MANULATEX chainmail shoulder glove.
Possibility to add a press-studs apron or a cover for maximum hygiene and ease of cleaning.
Blank stainless steel plate on the back (possibility of customized printing on demand)



NORMS & REGULATIONS

This tunic complies with the regulation (UE) EPI 2016/425 (2016).


EN ISO13998 (2003) performance **level 2** : suitable for boning operations.

Notified body in charge of the certification:

N° 2777 SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Co. Meath - D15 YN2P - Ireland

Notified body involved in manufacturing control: N° 0333 AFNOR certification

11 rue Francis De Pressensé - 93571 - La Plaine Saint-Denis



CLEANING CONDITIONS

Cleaning / Disinfection: PPE can be cleaned using a suitable washing gun, by soaking, by vigorous brushing or in a washing machine. In all cases, the water with added product must be at a maximum temperature of 63 ° C.

Warning : the technical sheet of the product used refers to a maximum water temperature, which may be lower.

Particular attention to dosage and temperature must be observed in the case of using alkaline chlorinated or acidic products.

Use only products authorized by the veterinary services. The use of chlorine in large doses and at high temperature is not recommended.

Disinfection: High temperature disinfection can be done with clean water of a minimum of 82 ° C up to a maximum temperature of 90 ° C, in a machine, by soaking or sprinkling.

Drying and Storage: Forced drying by hot or natural air ventilation but in a dry and ventilated place. Store in a cool, dry place

SIZE AND REFERENCES: * Height from top of the shoulder

Width x height* (cm)	Reference	Weight (grams)	Height (cm)	Waist / chest measurement (cm)
56 x 85	OXTU730.7M1.000XXX	1 800 g	148-165	90-120
56 x 100	OXTU730.7M4.000XXX	2 070 g	158-200	90-120
56 x 115	OXTU730.7M7.000XXX	2 250 g	165-220	90-120
64 x 115	OXTU730.7L7.000XXX	2 520 g	165-220	100-140

N° intrastat : 73239390



Adresse postale : CS 40055 - 49170 - SAINT-GEORGES-SUR-LOIRE - France - E-mail : manulutex@manulutex.fr - Internet : www.manulutex.fr
Site de Champocé-sur-Loire : 1 Rue du Mille - 49123 CHAMPTOCÉ-SUR-LOIRE - France - Tel : +33 (0)2 41 39 90 30 -
Site de St-Germain-des-Près : Zone Artisanale La Potherie - 49170 ST-GERMAIN-DES-PRÉS - Tel : +33 (0)2 41 39 90 30
SAS au capital de 125 000 € - R.C.S. Angers B 332 107 036 (85 B 112) - Siret 332 107 036 00029 - APE 3299Z - TVA FR 73 332 107 036 - EORI FR 332 107 036 00029