

JULIET APRON WITH SLEEVES

PPE - category I



FIELD OF APPLICATION

JULIET apron is resistant to standard cleaning agents. It is appreciated for its flexibility, light weight and excellent tear resistance. Temperature range for use: -30°C to +90°C.

CLEANING CONDITIONS

Cleaning : wash and brush the apron in hot soapy water (40°C) or in a mixture of water and a gentle detergent. **Rinsing** : with water. Do not use toxic products to clean or rinse the apron. **Storage** : After cleaning, store in a dark, dry, well-ventilated place. The apron must be replaced when it shows signs of wear and tear.

With a proper use and a good maintenance, your apron lasts longer!

PERFORMANCE LEVELS

Type of test	Standard	Performance
Abrasion resistance	EN 12947-2	>100 000 frictions
Trapezoidal tear resistance	EN ISO 9073-4	>40 N
Tensile resistance	EN ISO 13934-1	>140N
Puncture resistance	EN 863	>20N

MATERIAL

polyurethane on polyamide support

FEATURES

- Colours : white, red, yellow, navy blue and khaki green
- Thickness : 400 µm (± 10%)
- Weight : 170 g/m² (± 10%)

- Standard dimensions (width x height in cm) :

- **SMALL** : for people measuring less than 1,70 m
- **MEDIUM** : for people measuring between 1,70 et 1,85 m
- **LARGE** : for people measuring more than 1,85 m

Aprons with stainless steel brass rings and eyelets.

Rear fastening with plastic hook and polyester braided elastic.

Wrist fastening with thick 3mm neoprene.

NORMS AND REGULATIONS

Base material in accordance with **EC N° 1935/2004 Regulation**, articles 3 and 4 on materials and articles intended to come into contact with food*.

Base material in accordance with **UE N°10/2011 Regulation** on rubber materials and articles intended to come into contact with food. This PPE may be put in fortuitous contact with all types of food*.

Apron in accordance with **Article 33 of the REACH Regulation N°1907/2006** and its amendments on products containing SVHC*.

(*) with the exception of neoprene wrist fastening.

This apron complies with the regulation **(UE) PPE 2016/425** and the standard **NF EN ISO 13688 (2013)**.

Claimed mechanical properties: abrasion, tear, tensile and puncture resistance.

