



OMEGA APRON

PPE - category I



FIELD OF APPLICATION

OMEGA apron is suitable for use in the food industry (high resistance to animal fats and blood). It is resistant to standard cleaning products. Temperature range for use: -20°C to +40°C.

CLEANING CONDITIONS

Cleaning : wash and brush the apron in hot soapy water (40°C) or in a mixture of water and a gentle detergent. **Rinsing** : with water. Do not use toxic products to clean or rinse the apron. **Storage** : After cleaning, store in a dark, dry, well-ventilated place. The apron must be replaced when it shows signs of wear and tear.

With a proper use and a good maintenance, your apron lasts longer!

PERFORMANCE LEVELS

| Type of test | Standard | Performance |
|-----------------------------|------------------|--------------|
| Abrasion resistance | EN 530 méthode 2 | >2000 cycles |
| Trapezoidal tear resistance | EN ISO 9073-4 | >80 N |
| Tensile resistance | EN ISO 13934-1 | >800N |
| Puncture resistance | EN 863 | >35N |

MATERIAL

Elastomere.

FEATURES

- Colours : white and blue
- Thickness : 350 µm (± 10%)
- Weight : 430 g/m² (± 10%)
- Standard dimensions (width x height in cm) : 90x115

Aprons with stainless steel brass rings and eyelets

Food safe polypropylene adjustment loop

Detectable plastic hook and polyester braided elastic

NORMS AND REGULATIONS

Base material in accordance with **EC N° 1935/2004 Regulation**, articles 3 and 4 on materials and articles intended to come into contact with food.

Base material in accordance with **UE N°10/2011 Regulation** on rubber materials and articles intended to come into contact with food. This PPE may be put in fortuitous contact with all types of food.

Apron in accordance with **Article 33 of the REACH Regulation N°1907/2006** and its amendments on products containing SVHC.

Does not contain phthalate, silicone (and silicone derivatives), or bisphenols

This apron complies with the regulation **(UE) PPE 2016/425** and the standard **NF EN ISO 13688 (2013)**.

Claimed mechanical properties: abrasion, tear, tensile and puncture resistance.

