

TUNIC WITH SPLIT LEG

with sleeves - PPE - category III



Ultralight sleeves for optimal comfort !

FIELD OF APPLICATION

The TPLUS tunic is made with 100% food contact approved stainless steel. It is used by butchers in meat industries, Horeca, supermarkets and many other fields such as textile industry... It ensures cut-protection against any risks with hand knives, hand cutting tools or stabbing.

CLEANING CONDITIONS

Cleaning / Disinfection : PPE can be cleaned using a suitable washing gun, by soaking, by vigorous brushing or in a washing machine. In all cases, the water with added product must be at a maximum temperature of 63 ° C. Warning : the technical sheet of the product used refers to a maximum water temperature, which may be lower. Particular attention to dosage and temperature must be observed in the case of using alkaline chlorinated or acidic products. Use only products authorized by the veterinary services. The use of chlorine in large doses and at high temperature is not recommended. **Disinfection :** High temperature disinfection can be done with clean water of a minimum of 82 ° C up to a maximum temperature of 90 ° C, in a machine, by soaking or sprinkling. **Drying and Storage :** Forced drying by hot or natural air ventilation but in a dry and ventilated place. Store in a cool, dry place.

SIZES AND REFERENCES

| Sleeves | Width x Height (cm) | Reference | Weight (grams) | Operator's size (cm) | Waist / Chest measurement (cm) |
|---------------|---------------------|--------------------|----------------|----------------------|--------------------------------|
| Sleeves 55 cm | 50 x 100 | OXTU730.8S4.710DG5 | 2580 g | 148 - 190 | 80 - 110 |
| Sleeves 65 cm | 56 x 115 | OXTU730.8M7.710DG5 | 3140 g | 158 - 220 | 90 - 120 |
| | 56 x 125 | OXTU730.8M9.710DG5 | 3260 g | 165 - 220 | 90 - 120 |
| | 64 x 125 | OXTU730.8L9.710DG5 | 3500 g | 165 - 220 | 100 - 140 |

MATERIAL

Food contact stainless steel chainmail.

FEATURES

Bust :

- Wire diameter : 0,5 mm
- Ring internal diameter : 3 mm
- Ring external diameter : 4 mm

Sleeves :

- Wire diameter: 0,4 mm
- Ring internal diameter : 3,2 mm
- Ring external diameter : 4 mm

Ultralight sleeves.

Straps attached to the tunic with stainless steel plates.

Adjustable waist belt and back strap 100 % polyurethane (food contact according to EU regulation 10/2011) and polyacetal buckles. Equipped with straps on the thighs and calves.

Self-closing wrist closure system with stainless steel spring.

Blank stainless steel plate on the back (possibility of customized printing on demand).

Possibility to add a press-studs apron for maximum hygiene and ease of cleaning.

NORMS AND REGULATIONS

This tunic complies with the regulation (UE) EPI 2016/425 (2016).

Bust : EN ISO13998 (2003) performance level 2 (suitable for boning operations).

Sleeve(s) : EN ISO13998 (2003) performance level 1.

Notified body in charge of the certification : N° 0556 Prüf und Zertifizierungsstelle Nahrungsmittel und Verpackung - Fachbereich Nahrungsmittel – Lortzingstrasse 2 - D – 55127 Mainz

Notified body involved in manufacturing control : N° 0333 AFNOR certification 11 rue Francis De Pressensé - 93571 - La Plaine Saint-Denis

